

CLAIMS

What is claimed is:

1. A freeway routing system for a field programmable gate array (FPGA), the
FPGA comprising:

5 a plurality of FPGA tiles, each FPGA tile comprising:
a plurality of functional groups (FGs) arranged in rows and
columns;
a plurality of interface groups (IGs) surrounding said plurality of
FGs such that one IG is positioned at each end of each row and column, each of
10 the IGs having a first, second and third set of input ports and a first, second and
third set of output ports;
a freeway set of routing conductors configured to transfer signals to the first,
second and third input ports of IGs in one FPGA, and configured to transfer
signals from said first, second and third output ports of the IGs of all other FPGA
15 tiles;

said freeway set of routing conductors comprising:

a plurality of vertical conductors that form intersections with
a plurality of horizontal conductors; and
programmable interconnect elements located at said
20 intersections in a diagonal orientation on said FPGA tile.

2. The FPGA of Claim 1, wherein said FPGA further comprises:

at least one other FPGA tile configured in the same manner as said first FPGA;

wherein the freeway set of routing conductors of each FPGA tile
5 are connected to any adjacent FPGA tile's freeway set of routing conductors.

3. The FPGA of Claim 2, wherein said FPGA further comprises:

programmable interconnect elements located at said connections
between adjacent FPGA tiles.

4. The FPGA of Claim 1, wherein said diagonally oriented programmable
10 interconnects are arranged from the upper left corner of said first FPGA tile to the lower right corner of said first FPGA tile.

5. The FPGA of Claim 1, wherein said diagonally oriented programmable
interconnects are arranged from the upper right corner of said first FPGA tile to the lower left corner of said first FPGA tile.

15 6. The FPGA of Claim 1, wherein said freeway set of routing conductors are further configured to also transfer signals from output ports of at least one IO.

7. The FPGA of Claim 1, wherein said freeway set of routing conductors are further configured to also transfer signals from output ports of at least one RAM.

8. A method of routing the internal components in a FPGA tile comprising:

20 inputting a function netlist defining a user circuit;

2057189-01500
2057189-01500

optimizing said user circuit;

placing user cells defining said user circuit into said FPGA internal components;

using a first set of routing conductors to route said user circuit to

5 interconnect said internal components to implement said user circuit; and

engaging a freeway set of routing conductors to meet said user circuit routing requirements;

generating a programming bitstream defining said user circuit; and

programming said FPGA functional unit with said bitstream to

10 implement said user circuit.

9. A method of routing the internal components in a FPGA tile comprising:

inputting a function netlist defining a user circuit;

optimizing said user circuit;

placing user cells defining said user circuit into said FPGA internal

15 components;

using a first set of routing conductors and a freeway set of routing

conductors to route said user circuit to interconnect said internal components to implement said user circuit;

generating a programming bitstream defining said user circuit; and

205720" 687200T
1007189 024502

programming said FPGA functional unit with said bitstream to
implement said user circuit.

10. A method of providing a freeway interconnect structure in a FPGA
comprising:

5 providing a plurality of FPGA tiles;

providing a plurality of functional groups (FGs) arranged in rows
and columns on each said FPGA tile;

providing a plurality of interface groups (IGs) surrounding said
plurality of FGs such that one IG is positioned at each end of each row and
10 column, each of the IGs having a first, second and third set of input ports and a
first, second and third set of output ports;

providing a freeway set of routing conductors configured to
transfer signals to said first, second and third input ports of IGs of one FPGA tile,
and configured to transfer signals from said first, second and third output ports
15 of IGs of all other FPGA tiles;

said act of providing a freeway set of routing conductors
comprising:

providing a plurality of vertical conductors that form
intersections with a plurality of horizontal conductors; and

205720" 68T 2200T
1007189-021502

providing programmable interconnect elements located at
said intersections in a diagonal orientation on said FPGA tile.

11. The method of Claim 10 further comprising:

providing at least one other FPGA tile configured in the same
5 manner as said first FPGA; and
connecting said freeway set of routing conductors of each FPGA
tile to any adjacent FPGA tile's freeway set of routing conductors.

12. The method of Claim 11, further comprising:

providing programmable interconnect elements located at said
10 connections between adjacent FPGA tiles.

13. The method of Claim 10, further comprising configuring said freeway set
of routing conductors to also transfer signals from output ports of at least one
IO.

14. The method of Claim 10, further comprising configuring said freeway set
15 of routing conductors to also transfer signals from output ports of at least one
RAM.

15. An apparatus for routing the internal components in a FPGA tile
comprising:

means for inputting a function netlist defining a user circuit;
20 means for optimizing said user circuit;

means for placing user cells defining said user circuit into said
FPGA internal components;

means for using a first set of routing conductors to route said user
circuit to interconnect said internal components to implement said user circuit;

5 means for determining whether the routing requirements of said
user circuit have been met using said first set of routing conductors;

means for engaging a freeway set of routing conductors to meet
said user circuit routing requirements;

10 means for generating a programming bitstream defining said user
circuit; and

means for programming said FPGA functional unit with said
bitstream to implement said user circuit.

16. An apparatus for routing the internal components in a FPGA tile
comprising:

15 means for inputting a function netlist defining a user circuit;

means for optimizing said user circuit;

means for placing user cells defining said user circuit into said
FPGA internal components;

1007189-021500
205120" 081200T

means for using a first set of routing conductors and a freeway set of routing conductors to route said user circuit to interconnect said internal components to implement said user circuit;

means for generating a programming bitstream defining said user
5 circuit; and

means for programming said FPGA functional unit with said bitstream to implement said user circuit.

205120" 68T4.00T
1007189-02150